Reinforcement Continuity Systems

ENQUIRY/ORDER FORM

Please photocopy this page and use it to detail your enquiry/order.



Type AU U Bar



Type U U Bar



Type A Straight Bar



Type AA Double Straight Bar



Type L Angle



Type LJ Double Angle



Type LL Double Angle

Item	Qty	Box Width (1) (mm)	Bar Dia 10, 12 (mm)	Stirrup Spacing (2) (mm)	Stirrup Type (see above)	Box Length (3) (mm)	Embedment Depth h (mm)	Pullout Leg Length l (mm)	Stirrup Width (4) c (mm)	Cog Length b (mm)
Re-bending Tool										

(1) Standard box widths 85, 120, 150, 190, 220mm.

(2) Variable stirrup spacing available. Standard spacing 150, 200mm.

(3) Standard lengths are 1000mm and 1200mm. Other sizes are available on request.

(4) Standard stirrup widths 100, 120, 150, 180mm.

Note: *Bars must be straightened using a Keybox re-bending tool. Do not straighten bars more than once.*

Date ❒ Order ❒ Enquiry

Company

Address

Town Post Code

Contact

Tel Fax

Delivery Date

Delivery Address

Town Post Code

Contact

Tel Fax

Project

If you would like help in creating a schedule of keyboxes and a programme for delivery for your project, please contact your local Ancon office.